

2009 BMW R 1200 GS Adventure

MSRP: \$16,750.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Air-cooled/oil-cooled Boxer twin-cylinder	Front Wheel	2.50 x 19 cross-spoke
Bore x Stroke	101.0 mm x 73.0 mm	Rear Wheel	4.00 x 17 cross-spoke
Displacement	1170 cc	Front Tire	110/80 x 19 tubeless
Horsepower	105 bhp @ 7500 rpm	Rear Tire	150/70 x 17 tubeless
Torque	85 lb/ft @ 5750 rpm	Dimensions	
Compression Ratio	12.0 :1	Overall Length	88.6 inches
Valve Gear	Chain-driven, high cam, OHV, w/adj. rocker arms	Overall Width	37.6 inches
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase	59.5 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	4.2 quarts	Seat Height	35.2 inches
Engine Management	BMW Engine Controller - BMS K	Steering Angle	63.8 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	3.8 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	492 lbs. excluding options&accessories
Fuel Capacity	8.7 U.S. gallons including 1 gallon reserve	Weight - Wet	564 lbs. excluding options&accessories
Charging System	720 Watts @ 14 Volts	Maximum Load	1045 lbs. GVWR
Battery	12 Volts 14 Amps/hour low maintenance	Standard Colors	
Cooling System	Air and thermostatically controlled oil cooling	Code Price	Description
Drivetrain		N15 N / C	Magma Red
Primary Drive	1:1.737	N32 N / C	Magnesium Metallic
Clutch	180 mm dry, single plate with hydraulic actuation	Standard Equipment	
1st Gear Ratio	2.37:1	631 N / C	Enduro Transmission
2nd Gear Ratio	1.64:1	771 N / C	Cross-Spoke Wheels
3rd Gear Ratio	1.29:1	Available Equipment	
4th Gear Ratio	1.06:1	350 \$150	Chrome Exhaust
5th Gear Ratio	0.93:1	416 \$800	Enduro ESA
6th Gear Ratio	0.84:1	519 \$250	Heated Hand Grips
Final Drive System	Enclosed driveshaft with two universal joints	530 \$250	Tire Pressure Monitor (TPM)
Final Drive Ratio	2.91:1	539 \$295	On Board Computer
Frame and Suspension		562 \$450	Fog Light
Frame	Tubular steel trellis frame	603 \$395	Anti-Theft Alarm
Front Suspension	BMW Telelever	630 \$1100	Integral ABS II (Disconnectable)
Front Travel	8.3 inches	633 N / C	Off-Road Tires
Rear Suspension	BMW EVO Paralever	650 \$400	Enduro ASC
Rear Travel	8.7 inches	680 \$350	Saddle Bag Mounts
Brakes			
Brake System	BMW		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.0 inch Dual Rotors		
Rear Brake	Single, two-piston floating caliper		
Rear Rotor	10.4 inch single, fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		