

2009 BMW G 650 Xcountry

MSRP: \$7,500.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Liquid-cooled single-cylinder	Front Wheel	2.50 x 19 wire-spoke
Bore x Stroke	100.0 mm x 83.0 mm	Rear Wheel	3.00 x 17 wire-spoke
Displacement	652 cc	Front Tire	100/90 x 19 tube-type
Horsepower	53 bhp @ 7000 rpm	Rear Tire	130/80 x 17 tube-type
Torque	44 lb/ft @ 5250 rpm	Dimensions	
Compression Ratio	11.5 :1	Overall Length	86.0 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	35.7 inches
Valves	2 x 36 mm intake / 2 x 31 mm exhaust	Wheelbase	59.0 inches
Valves / Cylinder	Four	Ground Clearance	Info. Unavailable
Engine Oil Capacity	2.4 quarts	Seat Height	33.1 inches
Engine Management	BMW Motor Controller - Compact (BMS-C II)	Steering Angle	61.5 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and external filter	Weight - Dry	326 lbs. excluding options & accessories
Fuel Capacity	2.5 U.S. gallons including one gallon reserve	Weight - Wet	353 lbs. excluding options & accessories
Charging System	280 Watts @ 14 Volts	Maximum Load	739 lbs. GVWR
Battery	12 Volts 10 Amps/hour maintenance-free		
Cooling System	Single Radiator, 50/50 water/anti-freeze mix	Code Price	Description
Drivetrain		N31 N / C	Sunset Yellow / White Aluminum Metallic
Primary Drive	1:1.946	Standard Equipment	
Clutch	Multiple plate in oil bath	588 N / C	White Turn Signals
1st Gear Ratio	2.75:1	Available Equipment	
2nd Gear Ratio	1.75:1	524 \$900	ABS
3rd Gear Ratio	1.31:1		
4th Gear Ratio	1.05:1		
5th Gear Ratio	0.84:1		
6th Gear Ratio	N/A		
Final Drive System	Chain		
Final Drive Ratio	2.937:1		
Frame and Suspension			
Frame	Steel bridge tubular frame		
Front Suspension	UPSD fork 45 mm		
Front Travel	9.4 inches		
Rear Suspension	Aluminum two unit cast swing arm, air damping		
Rear Travel	8.3 inches		
Brakes			
Brake System	Front and rear disc with optional ABS		
Front Brakes	One two piston caliper		
Front Rotor	11.8 inch fixed rotor		
Rear Brake	One, single-piston floating caliper		
Rear Rotor	9.5 inch fixed rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		