

2009 BMW K 1200 LT

MSRP: \$21,520.00* Destination charge (not included in MSRP): \$495



Copyright 2008 BMW of North America, LLC., Woodcliff Lake, New Jersey all rights reserved.
 *Actual price determined by dealer. Price excludes taxes, license, options and handling charge.
 Prices and specifications subject to change without notice.

Engine		Wheels and Tires	
Type	Liquid-cooled inline four-cylinder	Front Wheel	3.50 x 17 cast alloy, five double-spoke
Bore x Stroke	70.5 mm x 75.0 mm	Rear Wheel	5.00 x 17 cast alloy, five, double-spoke
Displacement	1172 cc	Front Tire	120/70 x 17 tubeless
Horsepower	116 bhp @ 8000 rpm	Rear Tire	160/70 x 17 tubeless
Torque	86 lb/ft @ 5250 rpm	Dimensions	
Compression Ratio	10.8 :1	Overall Length	98.5 inches
Valve Gear	DOHC, chain-driven with bucket tappets	Overall Width	42.5 inches
Valves	2 x 26.5 mm intake / 2 x 23 mm exhaust	Wheelbase	64.1 inches
Valves / Cylinder	Four	Ground Clearance	3.5 inches
Engine Oil Capacity	4.0 quarts	Seat Height	30.3 inches
Engine Management	Motronic MA 2.4	Steering Angle	63.0 degrees
Fuel Requirement	Premium Unleaded	Front Wheel Trail	4.6 inches
Fuel Tank	HDPE, internal pump and internal filter	Weight - Dry	761 lbs. excluding options & accessories
Fuel Capacity	6.2 U.S. gallons including 1 gallon reserve	Weight - Wet	835 lbs. excluding options & accessories
Charging System	840 Watts @ 14 Volts	Maximum Load	1322 lbs. GVWR
Battery	12 Volts 19 Amps/hour	Standard Colors	
Cooling System	Dual radiators, 50/50 water/anti-freeze mix	Code Price	Description
Drivetrain		716 N / C	Night Black Non-Metallic
Primary Drive	1:1.889 with reverse gear 116:1	Standard Equipment	
Clutch	180 mm dry, single plate with hydraulic actuation	320 N / C	Xenon Light
1st Gear Ratio	2.05:1	394 N / C	Preparation for BMW Motorrad Navigator
2nd Gear Ratio	1.60:1	417 N / C	Central Locking
3rd Gear Ratio	1.27:1	418 N / C	Ground Lighting
4th Gear Ratio	0.96:1	445 N / C	Top Case Rack with Brake Light
5th Gear Ratio	0.70:1	496 N / C	Soft Touch Seat
6th Gear Ratio	N/A	518 N / C	Heated Seats and Passenger Backrest
Final Drive System	Enclosed driveshaft with two universal joints	519 N / C	Heated Hand Grips
Final Drive Ratio	2.75:1	538 N / C	Cruise Control
Frame and Suspension		553 N / C	Tall Windshield
Frame	Central beam cast alum. w/ steel tube rear frame	603 N / C	Anti-Theft Alarm
Front Suspension	BMW Telelever	765 N / C	Dual Accessory Socket
Front Travel	4.0 inches	773 N / C	Seat - Black
Rear Suspension	BMW Paralever		
Rear Travel	5.1 inches		
Brakes			
Brake System	BMW EVO with full integral ABS		
Front Brakes	Two, four-piston fixed calipers		
Front Rotor	12.6 inch dual floating rotors		
Rear Brake	Single, four-piston fixed caliper		
Rear Rotor	11.2 inch single floating rotor		
Actuation Method	Hydraulic, DOT 4 fluid type		